











## Features

- Pure sine wave inverter
- PV invput 120-500Vdc
- Built-in Wifi for monitoring data
- Configurable battery & AC/Solar charger priority

## ■ Working with or without battery



- (MPPT) Built-in 100A MPPT
- User friendly LCD operation
- Wall mount design, Easy installation
- Battery equalization extends lifecycle

## ■ Built-in Wifi for monitoring data





| Model                              | SP520-3500-24H  | SP520-5500-48H                    |
|------------------------------------|---|-----------------------------------|
| Rated Power                        | 3500W/3500VA  | 5500W/5500VA                      |
| Input                              |   |                                   |
| Rated Input Voltage                | 230VAC  |                                   |
| Selectable Voltage Range           | 170~280VAC(For personal computers) ;90~280VAC (For home applications) |                                   |
| Frequency                          | 50Hz/60Hz(Auto sensing)   |                                   |
| Output                             |   |                                   |
| Waveform                           | Pure sine wave  |                                   |
| AC Voltage Regulation (Batt, Mode) | 230VAC±5%   |                                   |
| Peak Power                         | 7000VA  | 11000VA                           |
| Load Capacity of Motors            | 2HP   | 4HP                               |
| Switch Time                        | 10ms (For personal computers);20ms (For home applications)            |                                   |
| Effiency                           | 98%   |                                   |
|                                    | Battery   |                                   |
| Battery Type                       | Lithium battery/Lead acid battery                                     | Lithium battery/Lead acid battery |
| Battery Voltage                    | 24VDC   | 48VDC                             |
| Constant Charging Voltage          | 29.2V   | 58.4V                             |
| Floate Charging Voltage            | 27VDC   | 54VDC                             |
| Overcharge Protection              | 33VDC   | 63VDC                             |
| PV&AC Charger                      |   |                                   |
| Max.PV Array Power                 | 5000W   | 6000W                             |
| MPPT Voltage Range                 | 120~450VDC  |                                   |
| Max.Voltage of Open Circuit        | 500VDC  |                                   |
| Max.PV Charging Current            | 100A  |                                   |
| Max.AC Charging Current            | 80A   |                                   |
| Max.Charging Current               | 100A  |                                   |
| General                            |   |                                   |
| Dimension D*W*H(mm)                | 120*322*416   |                                   |
| Weight                             | 9   | 10                                |
| Protection Degree                  | IP21  |                                   |
| Operating Temperature Range        | -10~50°C  |                                   |
| Storage Temperature Range          | -15~60°C  |                                   |
| Noise                              | <60dB   |                                   |
| Cooling Method                     | Fan cooling   |                                   |
| Interface                          |   |                                   |
| Communication                      | Rs232, WIFI   |                                   |

1 | 2 | **SP520 Series** 



## FRECON ELECTRIC (SHENZHEN) CO.,LTD

Add: 2nd floor, Building 3, Zhenbao Industrial Zone, Shiyan Street, Baoan District, Shenzhen, China

Tel: (+86) 755-88605930 Fax: (+86) 755-88606072 E-Mail:overseas@frecon.com.cn Web: www.frecon-inverter.com





Website Fa 202407(V1.4)